



لفائدة وبالإنابة عن شركة قطر للبترول acting for and on behalf of Qatar Petroleum for the
 لبيع المنتجات البترولية المحدودة Sale of Petroleum Products Company Limited

STANDARD SPECIFICATION QATAR MARINE CRUDE OIL

These specifications are for information purposes only and shall not be binding upon the Seller. The Seller will bear no liability for delivering crude that doesn't conform to these specifications.

Test	Method	Unit	Value
API Gravity @ 60 ^o F	Calculated	° API	32 - 31.0*
Density @ 15 ^o C	ASTM D5002	kg/L	0.8702
Specific Gravity @ 60/60 ^o F	Conversion	-	0.8707
Total Sulphur	ASTM D4294	% Wt.	2.17
Mercaptan Sulphur	UOP 163	ppm wt.	230
Hydrogen Sulphide	UOP 163	ppm wt.	320
Total Acid Number	ASTM D664	mgKOH/g	0.15
Pour Point	ASTM D 5853	°F	-5.8
Reid Vapour Pressure	ASTM D5191	psi	4.65
Kinematic Viscosity @ 15 ^o C	ASTM D445	cSt	23.41
Salt Content	ASTM D3230	PTB	76.0
Wax Content	UOP 46	% Wt.	6.05
Water Content	ASTM D4006	%Vol.	0.0

*The API may vary due to weather conditions and/or mix of different grades of crude.

